

<b>Machine</b>	Pro Eco
<b>Description</b>	0.250" X 62"
<b>Products</b>	Cold rolled steel Hot rolled pickled and oiled steel Hot rolled pickled dry steel Galvanized Steel Galvanneal Steel Cold Rolled Full Hard Aluminum
<b>Characteristics</b>	<ul style="list-style-type: none"> <li>• Material can be processed with off-cuts</li> <li>• Entry and exit crop shear</li> <li>• Please inquire for slitting, sidetrimming or packaging outside of specification</li> </ul>
<b>Yield Strength</b>	0.250" @ 90,000 PSI

<b>Slitting Capacity</b>	0.060	0.100	0.180	0.250
50-60 KSI Tensile Strength	22	16	11	6
60-70 KSI Tensile Strength	20	14	9	5
70-80 KSI Tensile Strength	15	12	7	4
80-90 KSI Tensile Strength	12	8	5	3

<b>Master Coil Capacity</b>	Min.	Max.
Coil weight	—	60,000
Thickness	0.060	0.250
Width	12.000	62.000
Int. diameter	20.000	30.000
Out. diameter	38.000	72.000

<b>Slitting Limits</b>		
Width	1.500	61.500
Required scrap	0.375	1.000



Pro Eco - Stoney Creek